



Captivate



Ice




Linen



Nordic Sky



Wheat



Granite



Nashi Pear



Summit



Citrus



Platinum



Apple




Ocean



Rosso



Ash



Moss



Sapphire



Eggplant



Midnight

This guide is a representation of fabric colour only. Contact your CSR Martini Representative for fabric samples. Due to the inherent nature of the fabric, colour variation may exist from samples and between rolls and batches.



Captivate

Our dECO Fabric Captivate range offers bold modern colours with a palette of neutrals. The soft, plush feel of Captivate adds an opulent surface texture to any interior. Captivate is inherently durable, does not fray and is Velcro® receptive, offering unlimited styling possibilities.

Applications

Multi-purpose interior fit out fabric. Designed for use on dECO absorptive acoustic panels and screens for use in office, commercial and residential interiors.

Sustainable Design

dECO Fabric is certified EPD, Green Tag^{Cert™} GreenRate Level A. Suitable for use in Green StarTM projects. Green Tag^{Cert™} is a certification and rating tool for building professionals approved by the Green Building Council of Australia (GBCA) and the Green Building Council of New Zealand (NZGBC).

Fabric Care

Vacuum regularly using an upholstery attachment on low suction. Do not use a vacuum attachment with a rotary brush. Brushing may damage the nap or character of the fabric. Treat spills and stains as soon as possible by using a damp cloth. Dry cleaning fluid can also be used. Do not rub or use an excessive amount of water. Blot the excess moisture with a dry clean cloth.

Physical Description and Properties

Thickness / width:	3 - 4 mm / 1350mm			
Melting point:	255°C			
Vapour pressure:	Not applicable			
Volatiles:	Nil			
Flash point:	More than 420°C			
Other properties:	Non-allergenic, low irritant, low flame response, resilient			
Ingredients:	Organic, long chain synthetic polymers			
Alkalinity:	pH 7.8 (pH 7 is neutral)			
Moisture absorption:	Exposure to an atmosphere of 50°C & 95% RH for four days gives moisture absorption of less than 0.2% by volume			
Colour fastness to light:	Greater than 7. Tested to ISO 105/B02: 1994 (Blue Scale)			
	Tested to and complies with AS ISO 9705		Group 1	
Fire resistance:	The following results were obtained when subjected to early fire hazard testing in accordance with Australian Standard AS 1530.3		Ignitability	0
			Spread of Flame	0
			Heat Evolved	0
			Smoke Developed	5

Disclaimer: The contents of this brochure are copyright protected and may not be reproduced in any form without prior written consent of CSR Martini. Recommendations and advice regarding the use of the products described in this brochure are to be taken as a guide only, and are given without liability on the part of the company or its employees. We reserve the right to change product specifications without prior notification, please refer to the CSR Martini website for the latest version of this document. The purchaser should independently determine the suitability of the product for the intended use and application.

www.csrmartini.com.au