

dECO Flex 7mm

- Flexible wall finish for straight and curved walls.
- Velcro® receptive surface.

Applications

Used in operable wall construction as a lining.

Decorative Finishes

dECO Flex is available in dECO Captivate fabric. dECO Captivate is a non-woven fabric with nap and no pattern repeat. Refer to our dECO Captivate Colour Guide for colour palette options.

Environmental Benefits and Credentials

dECO Flex is manufactured from thermally bonded polyester fibre with a minimum of 60% recycled fibre content from PET packaging such as empty drink bottles.

- GreenTag^{Cert™} certified
- Environmental Product Declaration (EPD) Certified in accordance with ISO 14025
- Product Health Declaration (PHD) certified
- Suitable for Green Star™ projects
- No red list chemicals are present
- No ozone-depleting gases are used during the manufacturing process
- Volatile organic compounds (VOCs) generated in the manufacturing process is classified as low (0.01 mg/m³)s
- Safe, non-irritant, non-toxic, and non-allergenic
- Products are 100% recyclable
- High reuse potential

Martini's Product Stewardship Program can be viewed at www.csmartini.com.au.



Product Specifications

dECO Flex Colour	Thickness (mm)	Width (m)	Standard Roll Length (m)*	Product Code
Apple	7 mm	1.22 m	25 m	166930
Ash	7 mm	1.22 m	25 m	166909
Citrus	7 mm	1.22 m	25 m	166967
Eggplant	7 mm	1.22 m	25 m	166969
Granite	7 mm	1.22 m	25 m	166906
Ice	7 mm	1.22 m	25 m	166905
Linen	7 mm	1.22 m	25 m	166921
Midnight	7 mm	1.22 m	25 m	166910
Moss	7 mm	1.22 m	25 m	166961
Nashi Pear	7 mm	1.22 m	25 m	166922
Nordic Sky	7 mm	1.22 m	25 m	166962
Ocean	7 mm	1.22 m	25 m	166964
Platinum	7 mm	1.22 m	25 m	166908
Rosso	7 mm	1.22 m	25 m	166968
Sapphire	7 mm	1.22 m	25 m	166965
Summit	7 mm	1.22 m	25 m	166963
Wheat	7 mm	1.22 m	25 m	166966

Tolerance in sizes: thickness +/- 2mm; width +/- 5mm. *Please note that due to the nature of the manufacturing process, there is a 10% over or under supply. Other roll lengths available upon request. Minimum length 7m.

Physical Description and Properties

Melting point:	250°C	
Vapour pressure:	Not applicable	
Other properties:	Non-allergenic, low irritant, low flame response, resilient	
Ingredients:	Organic, long chain synthetic polymers	
Max service temp:	110°C	
Alkalinity:	pH 7.8 (pH 7 is neutral)	
Thermal performance:	R 0.24 tested to 15°C	
Colourfastness to light:	Greater than 7 tested to ISO 105/B02: 1994	
Colourfastness to rubbing:	5 (Dry) 5 (Wet) tested to ISO 105-X12: 2001	
Moisture absorption:	Exposure to an atmosphere of 50°C and 95% relative humidity for four days gives moisture absorption of less than 0.2% by volume	
Fire resistance:	Tested to AS ISO 9705 Corner Burn in accordance with AS 5637.1	Group 1 SMOGRA not more than 100 m ² /s ² x 1000

Disclaimer: The contents of this brochure are copyright protected and may not be reproduced in any form without prior written consent of CSR Martini. Recommendations and advice regarding the use of the products described in this brochure are to be taken as a guide only, and are given without liability on the part of the company or its employees. We reserve the right to change product specifications without prior notification, please refer to the CSR Martini website for the latest version of this document. The purchaser should independently determine the suitability of the product for the intended use and application.