



# Martini dECO FLEX

Flexible Fabric wall finish for reducing echo  
and reverberation

[csmartini.com.au](http://csmartini.com.au)



CSR Martini Pty Limited  
P.O. Box 560, Ingleburn NSW 1890  
[martinienquiries@csr.com.au](mailto:martinienquiries@csr.com.au)  
1300 767 776





## Application

Used in education, child care centres, libraries, offices and public spaces.

## Environmental Benefits and Credentials

- GreenTag<sup>Cert</sup>™ certified
- Environmental Product Declaration (EPD)  
Certified in accordance with ISO 14025
- Product Health Declaration (PHD) certified
- Declare certified
- Suitable for Green Star™ projects
- No red list chemicals are present
- No ozone-depleting gases are used during the manufacturing process
- Volatile organic compounds (VOCs) generated in the manufacturing process is classified as low (0.01 mg/m<sup>3</sup>)s
- Safe, non-irritant, non-toxic, and non-allergenic
- Products are 100% recyclable
- High reuse potential



## Size/Thickness

Thickness: 10-12mm

Standard roll size: 1220mm x 25m

## Finish/Colour

Available with Martini dECO Captivate.

## Fire Resistance

Test Standard	AS ISO 9705 – 2003	ISO 9705:1993
Building Code	NCC C1.10	NZBC C/VM2
Classification	Group 1 SMOGRA < 100m <sup>2</sup> /s <sup>2</sup>	Group 1-S Smoke Prod Rate < 5m <sup>2</sup> /s <sup>2</sup>

## Acoustic Performance

Frequencies	125hz	250hz	500hz	1,000hz	2,000hz	4,000hz	NRC
10-12mm	0.05	0.10	0.30	0.50	0.75	0.95	0.40

Tested to AS/ISO 354:2006.

For more information on dECO FLEX refer to the data sheet available for download on our website;  
<http://www.csrmartini.com.au/downloads>

