



# Martini dECO SCREEN

Decorative sound absorbing panel designed  
for workstations with fabric finish to both sides

[csmartini.com.au](http://csmartini.com.au)

AUSTRALASIA **EPD**®

**EPD**®  
THE INTERNATIONAL EPD® SYSTEM

**Declare.**

CSR Martini Pty Limited  
P.O. Box 560, Ingleburn NSW 1890  
[martinienquiries@csr.com.au](mailto:martinienquiries@csr.com.au)  
1300 767 776





## Application

Pinable partitions in workstation systems in education, office, retail and commercial interiors.

## Environmental Benefits and Credentials

- GreenTag<sup>Cert</sup>™ certified
- Environmental Product Declaration (EPD) Certified in accordance with ISO 14025
- Product Health Declaration (PHD) certified
- Declare certified
- Suitable for Green Star™ projects
- No red list chemicals are present
- No ozone-depleting gases are used during the manufacturing process
- Volatile organic compounds (VOCs) generated in the manufacturing process is classified as low (0.01 mg/m<sup>3</sup>)s
- Safe, non-irritant, non-toxic, and non-allergenic
- Products are 100% recyclable
- High reuse potential



## Size/Thickness

Thickness: 12mm with dECO Embrace Fabric  
16mm with dECO Captivate Fabric

Standard panel size: 2420 x 1210mm

## Finish/Colour

Available on either a black or white base finished on both sides with Martini dECO Captivate or dECO Embrace fabric.

## Fire Resistance

<b>Test Standard</b>	AS ISO 9705 – 2003	ISO 9705:1993
<b>Building Code</b>	NCC C1.10	NZBC C/VM2
<b>Classification</b>	Group 1 SMOGRA < 100m <sup>2</sup> /s <sup>2</sup>	Group 1-S Smoke Prod Rate < 5m <sup>2</sup> / <sup>2</sup>

## Acoustic Performance

<b>Frequencies</b>	125hz	250hz	500hz	1,000hz	2,000hz	4,000hz	<b>NRC</b>
<b>dECO Screen</b>	0.05	0.10	0.0	0.70	0.90	0.95	<b>0.50</b>

Tested to AS/ISO 354:2006.

For more information on dECO SCREEN refer to the data sheet available for download on our website;  
<http://www.csmartini.com.au/downloads>