

## Martini dECO FELT

Flat acoustic fabric



C\$R



The dECO Felt colour range offers freshness and vitality to any interior space. Colours have been inspired by the beauty of our world. From calming palette of neutrals to vibrant pops of life, dECO Felt will elevate any design.

Snow	Neptune	Moss	Bolt
Lace	Nordic Sky	Apple	Bumble Bee
Porcelain	Summit	Citrus	Tiger
lce	Sapphire	Shamrock	Cherry
Granite	Ash	Ariel	Candy
Platinum	Pitch		

Martini dECO Felt



## Physical Description and Properties

Melting point:	250°C				
Flash point:	None allocated				
Other properties:	Non-allergenic, low irritant, low flame response, resilient				
Ingredients:	Organic, long chain synthetic polymer				
Max service temp:	110°C				
Alkalinity:	pH 7.8 (pH 7 is neutral)				
Moisture absorption:	Exposure to an atmosphere of 50°C and 95% RH for four days gives moisture absorption of less than 0.2% by volume				
Colour fastness to light:	Tested to Xenon arc ISO 105/B02 Blue Standard 7 and achieves Greater than 7				
Luminous reflectance:	As per ASTM E1477-98A: 2017				
	Apple	61.98	Moss	44.66	
	Ariel	53.08	Neptune	48.16	
	Ash	24.04	Nordic Sky	59.31	
	Bolt	47.98	Pitch	14.34	
	Bumble Bee	80.18	Platinum	13.10	
	Candy	36.31	Porcelain	82.23	
	Cherry	39.63	Sapphire	3.15	
	Citrus	54.56	Shamrock	57.08	
	Granite	59.42	Snow	91.12	
	lce	73.76	Summit	20.01	
	Lace	57.71	Tiger	58.44	

## csrmartini.com.au

CSR Martini Pty Limited P.O. Box 560, Ingleburn NSW 1890 martinienquiries@csr.com.au 1300 767 776

04/21









Disclaimer: The contents of this brochure are copyright protected and may not be reproduced in any form without prior written consent of CSR Martini. Recommendations and advice regarding the use of the products described in this brochure are to be taken as a guide only, and are given without liability on the part of the company or its employees. We reserve the right to change product specifications without prior notification, please refer to the CSR Martini website for the latest version of this document. The purchaser should independently determine the suitability of the product for the intended use and application.