



Martini dECO CEILING TILES

High performance acoustic ceiling tiles

A large, light blue, stylized 'm' graphic that spans the bottom half of the page.

CSR

dECO Ceiling Tiles

dECO Ceiling Tiles are durable acoustic ceiling tiles designed for standard drop-in ceiling grid systems.

- Easy drop-in ceiling tiles.
- Available in 22 colours from our dECO Felt colour range.

Applications

Suitable in a variety of spaces such as open plan offices, meeting rooms, boardrooms, break-out spaces, classrooms, auditorium, sport halls and lecture theatres.

Environmental Benefits and Credentials















Manufactured from thermally bonded polyester fibre with up to 80% recycled fibre content from post-consumer PET packaging such as empty drink bottles.

- GreenTag^{Cert}™ certified
- Environmental Product Declaration (EPD) Certified in accordance with ISO 14025
- Product Health Declaration (PHD) certified
- Declare certified
- Suitable for Green Star™ projects
- No red list chemicals are present
- No ozone-depleting gases are used during the manufacturing process
- Safe, non-irritant, non-toxic, and non-allergenic
- Products are 100% recyclable
- High reuse potential



Martini's Product Stewardship Program can be viewed at www.csrmartini.com.au

Finishes



Acoustic Performance

Frequencies	125hz	250hz	500hz	1,000hz	2,000hz	4,000hz	NRC
dECO Ceiling Tiles 25mm	0.80	0.80	0.80	0.95	1.00	0.95	0.90

Tested in accordance with AS/ISO 354:2006 with 400m plenum space

Physical Description and Properties

Composition:	100% Polyester Fibre (PET)		
Size:	1195mm x 595mm Tolerance: length +/- 10mm; width +/- 5mm		
Thickness:	25mm Tolerance: +/- 1mm		
Each/Box:	4 tiles per box		
Edge Details:	Square edge		
Luminous reflectance:	Refer to dECO Felt data sheet for details		
Moisture absorption:	Exposed to an atmosphere of 30°C at 90% Relative Humidity for 7 days gives moisture absorption of less than 0.003% by weight		
Warranty:	15 year product warranty		
Fire resistance:	Tested to AS ISO 9705 Corner Burn in accordance with AS 5637.1		Group 1 SMOGRA not more than 100m ² /s ² x 1000

csrmartini.com.au

CSR Martini Pty Limited
P.O. Box 560, Ingleburn NSW 1890
martinienquiries@csr.com.au
1300 767 776

04/21



Disclaimer: The contents of this brochure are copyright protected and may not be reproduced in any form without prior written consent of CSR Martini. Recommendations and advice regarding the use of the products described in this brochure are to be taken as a guide only, and are given without liability on the part of the company or its employees. We reserve the right to change product specifications without prior notification, please refer to the CSR Martini website for the latest version of this document. The purchaser should independently determine the suitability of the product for the intended use and application.